



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(51) International Patent Classification: <b>G01N 27/26; B01D 13/02</b>	<b>A1</b>	(11) International Publication Number: <b>WO 79/00002</b> (43) International Publication Date: <b>11 January 1979 (11.01.79)</b>
<p>(21) International Application Number: <b>PCT/GB78/00002</b></p> <p>(22) International Filing Date: <b>1 June 1978 (01.06.78)</b></p> <p>(31) Priority Application Number: <b>25043/77</b></p> <p>(32) Priority Date: <b>15 June 1977 (15.06.77)</b></p> <p>(33) Priority Country: <b>GB</b></p> <p>(71) Applicants: <b>NATIONAL RESEARCH DEVELOPMENT CORPORATION; P.O. Box 236, Kingsgate House, 66-74 Victoria Street, London, United Kingdom, SW1 E6SL (for all designated States except US). HAMPSON, Frank; 51 Grange Road, Lewes, Sussex, United Kingdom (for US only). MARTIN, Archer, John, Porter; Abbotsbury, Barnet Lane, Elstree, Hertfordshire, United Kingdom (for US only).</b></p>	<p>(72) Inventors: <b>HAMPSON, Frank; 51 Grange Road, Lewes, Sussex, United Kingdom. MARTIN, Archer, John, Porter; Abbotsbury, Barnet Lane, Elstree, Hertfordshire, United Kingdom.</b></p> <p>(74) Agent: <b>CRESPI, R.S.; National Research Development Corporation, Patent Department, P.O.Box 236, Kingsgate House, 66-74 Victoria Street, London, United Kingdom, SW1 E6SL.</b></p> <p>(81) Designated States: <b>CH (European patent), DE (European patent), FR (European patent), GB, GB (European patent), LU (European patent), SE (European patent), US.</b></p> <p>Published with: <i>International search report</i></p> <div data-bbox="1193 840 1446 976" style="border: 1px solid black; padding: 5px; text-align: center;"> <b>15 JAN 1979</b>          Int. Search Report       </div>	

BEST AVAILABLE COPY

(54) Title: **IMPROVEMENTS RELATING TO MEMBRANE ELECTROPHORESIS**

## (57) Abstract

The separation of substances by membrane electrophoresis using the principle of isoelectric focussing is improved by the use of membranes of known isoelectric point and having buffering capacity. When such membranes are arranged in series of increasing isoelectric point from the anode (+) to the cathode (-) in a pH gradient of increasing pH in the same direction, and each membrane is located between electrolyte zones having pHs respectively lower and higher than its isoelectric point, the tendency for electroendosmosis to occur during electrophoresis is substantially reduced. Methods for chemical treatment of agarose and other gel membranes to introduce acidic and basic groups so as to confer buffering power at the isoelectric point are described. These include the attachment of ampholytes to the gel by intermediate chemical linkages. Under varying chemical conditions membranes exhibiting isoelectric properties over a range of pH values can be prepared and specific values predetermined to within narrow limits. The membranes are used in multicompartament apparatus with separate cooling of individual circulating electrolyte zones and may be in the form of sheet membranes mounted in a nesting configuration one above the next with gravity flow of electrolyte and edge sealing between the membranes. High current and large scale use of the method for preparative as well as analytical purposes are envisaged.



***FOR THE PURPOSES OF INFORMATION ONLY***

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT

BR	Brazil
CF	Central African Empire
CG	Congo
CH	Switzerland
CM	Cameroon
DE	Germany, Federal Republic of
DK	Denmark
FR	France
GB	United Kingdom

JP	Japan
LU	Luxembourg
MG	Madagascar
MW	Malawi
SE	Sweden
SN	Senegal
SU	Soviet Union
TD	Chad
US	United States of America

IMPROVEMENTS RELATING TO MEMBRANE ELECTROPHORESIS

This invention relates to electrophoresis and more particularly to electrophoresis through membranes to effect isoelectric focussing.

Membrane electrophoresis is a known technique and various forms of electrophoresis apparatus have been proposed for both analytical and preparative purposes. These have been reviewed by A.J.P. Martin and R.L.M. Synge in "Advances in Protein Chemistry", Vol. 2, pages 31-38, Academic Press 1945 and R.L.M. Synge in Biochemical Journal 1951 49 643-650. So far, however, no apparatus has been available in which large quantities of material can be treated. Large scale work involves the use of high currents which inevitably generate much heat and therefore requires efficient cooling of the electrolytes for continuous operation. Furthermore, considerable problems exist in connection with membrane stability and performance.

The greatest of such problems is that of electroendosmosis, a term denoting bulk fluid flow through the membranes caused by the presence or acquisition of an electrical charge on the membrane. Not only is it difficult to prepare membranes which are initially free of electric charge but even where this can be achieved it is found that the membranes acquire charge by absorption of ions from



- 2 -

the electrolyte during the electrophoretic process. The charged membranes will tend to respond to the applied electric field but because they are not free to move with respect to the electrolyte the effect observed empirically is that of a corresponding movement of electrolyte through the membrane. The consequent flow of bulk electrolyte is unacceptable both because it destroys the stability of the carefully established pH gradient, an essential condition of electrophoresis, and because it causes remixing of the separated species. These effects can totally vitiate the electrophoretic effect.

10 The basic concept of the present invention is that of an electrophoresis membrane having a known isoelectric point and buffering capacity at its isoelectric point. Such a membrane, the electrophoretic characteristics of which are known and calibrated, has the property that when disposed in a pH gradient encompassing a narrow range about a specific pH, which can be designated as the isoelectric pH, there will be only a very small or virtually no net charge on the membrane. Because of its buffering power, the membrane will remain under stable substantially isoelectric conditions during the electrophoretic process and therefore there will be little or no tendency for electroendosmosis to occur during electrophoresis.

Membranes in accordance with this invention may be obtained by incorporating both positively and negatively charged species into the membrane, notably basic and acidic groups respectively, so as to induce a high density of charge of both signs, an appreciable number of which have a pK close enough, e.g. within about one pH unit, to the isoelectric point to exert buffering power. When such a membrane is placed in contact

- 3 -

with an electrolyte of a predetermined known pH there will be minimal net charge on the membrane. The membrane is thus internally buffered at its isoelectric point.

The approach taken by the present invention is based on the  
5 realisation that, in order to reduce or eliminate electroendosmosis, the membranes separating the compartments in a multi-compartment isoelectric focussing apparatus should possess the smallest possible or virtually no net charge at the pH prevailing in the pores of the membrane which of course will be for each membrane a value intermediate  
10 between the pHs on both sides of it. According to this invention the membranes possess a high density of charges of both signs and of appropriate ionization constant so that the membrane has a high buffering capacity at its isoelectric point and therefore absorption of ions will cause very small effects.

#### 15 MEMBRANE PREPARATION

The preparation of membranes in accordance with the invention may be carried out with well known and typical membrane-forming materials known to be suitable for electrophoresis purposes. Such materials include gel-forming polymers which are sufficiently  
20 chemically reactive to enable the introduction of ionisable radicals i.e. acid groups such as carboxylic, sulphonic, phosphonic groups and nitrogenous basic groups such as amino groups. Typical suitable materials are hydroxylic polymers including cellulose, modified cellulose, cross-linked polyvinyl alcohol and cross-linked polyethylene  
25 oxide. Cross-linked polyacrylamide gels suitably chemically modified may also be used. Especially good results have been obtained with agar or agarose gels. Conveniently these may be supported on porous



- 4 -

carrier substrates such as filter-paper, cotton or linen cloth, or other suitable web materials to provide adequate strength. Additionally, some cross-linking of the agar or agarose gels is advisable to withstand the chemical reaction conditions necessary for the

5 introduction of ionisable groups as hereinafter described.

The introduction of groups capable of generating negative ions may very conveniently be achieved by carboxyalkylation e.g. by treatment with a suitable salt or derivative of chloracetic acid to introduce the group  $-\text{CH}_2\text{COOH}$ . Likewise groups which can

10 give rise to positively charged species may be introduced by amino-alkylation e.g. by treatment with a diethylamino ethyl halide to introduce the group  $-\text{CH}_2\text{CH}_2\text{NEt}_2$ . In a modification of this method, more complex amino-containing radicals may be chemically combined with the membrane in a step-wise manner by reaction with a linking reagent

15 e.g. epichlorhydrin to introduce a substituent which is further reacted with a suitable amine e.g. diethanolamine. These methods are generally well known in the production of ion exchange and chromatographic materials and their application for the purposes of the present invention is relatively straightforward requiring, however, some

20 experimentation to determine the appropriately mild reaction conditions for use with the relatively delicate membrane structures. It has been found advantageous in practice to develop reaction conditions for the introduction of a standard level of carboxymethylation and then to adjust the isoelectric point of the membrane to any desired value

25 by introducing varying amounts of aminoalkyl or other amino-containing groups under controlled reaction conditions as determined by experiment. By way of example, filter paper supports impregnated with solutions



- 5 -

of agarose (4% w/v), soaked in aqueous alkali, and cross-linked by treatment with epichlorhydrin (1-chloro-2:3-epoxypropane) may be carboxymethylated by treatment with a solution of sodium chloroacetate (1M) in sodium hydroxide (1.5M) for two hours duration. Following this the membranes are aminoalkylated to varying extents by treatment with epichlorhydrin and varying amounts of diethanolamine (0.08M - 0.12M) under alkaline conditions giving rise to a series of isoelectric membranes over the pH ranges indicated below:

	<u>Ethanolamine molar concentration</u>	<u>Isoelectric pH (+ 0-1)</u>
10	0.08	4.8
	0.10	5.1
	0.12	5.5

It will be appreciated that isoelectric points on the alkaline side of neutrality may be achieved with the use of more severe aminoalkylation reaction conditions. The membranes produced by the modified method described will thus contain cross-linking groups of formula  $-\text{OCH}_2\text{CHOHCH}_2\text{O}-$  and substituent groups of formula  $-\text{CH}_2\text{COOH}$  (acid form) and  $-\text{OCH}_2\text{CHOHCH}_2\text{N}(\text{CH}_2\text{CH}_2\text{OH})_2$  (basic form).

In an alternative method, ampholytes i.e. substituents containing both acidic and basic groups can be attached to the membrane or membrane-forming substrate material by linking reagents such as epichlorhydrin in an extension of the method described above. Thus an ampholyte such as the reaction product of chloracetic acid and tetraethylene pentamine (a complex mixture of species of varied formulae one of which, for example, has the formula  $\text{HOOC} \cdot \text{CH}_2 \cdot \text{NH}(\text{CH}_2\text{CH}_2\text{NH})_4 \cdot \text{CH}_2\text{COOH}$ ) or an ampholyte commercially available under the Trade Mark Ampholine (LKB) may be combined with the membrane material through the reaction with epichlorhydrin in a

- 6 -

similar manner to that described above for diethanolamine. By using mixtures of such ampholytes of varying degrees of acidity or basicity the resulting pI of the membrane may be predetermined precisely or within a narrow range of pH. Values of pI over the range pH 4 to 6  
5 are conveniently obtained by this method.

Yet further methods may commend themselves to those skilled in the art and require only brief mention here. For example, charged molecules of higher molecular weight than the above-mentioned reagents may be incorporated physically into the membrane e.g. during casting  
10 or chemically linked to a gel activated with cyanogen bromide.

#### CALIBRATION

Following the general guidelines given above, and with practical experience, it is possible to prepare membranes to a predetermined pI value within an approximate range. Successive  
15 approximation methods may then be applied, using the electroendosmotic effect with a marker substance e.g. benzyl alcohol in a test series of membranes set up under practical conditions of electrophoresis. These are repeated until calibration to the required degree of precision is achieved. It will be appreciated that for most purposes  
20 it is not required to know the pI of the membrane with absolute precision, because this is often not necessary as a practical matter, and the knowledge of a narrow pH band in which the pI lies will suffice.

#### ELECTROPHORESIS METHOD

The isoelectric membranes of the present invention, which may be  
25 alternatively described as ampholyte membranes, are intended to be used in a graded series of increasing isoelectric point from anode (+ electrode) to cathode (- electrode) each membrane separating





- 7 -

electrolyte compartments having a pH respectively below the isoelectric point pI of the membrane on its anodic side and above the pI on its cathodic side. The electrolyte pH difference between both sides of each of the successive membranes may be adjusted to suit the purposes of the particular separation being considered; the more gradual this is in the series the more the resolving power of the particular apparatus. Differences in pH of the order of 0.5 units have been found suitable.

The number of membranes involved will also depend on the complexity of the separation. In one of the simpler separations where recovery of only one component is necessary, the others being discarded, the use of two isoelectric membranes will often be sufficient. In most cases more than two will be desirable.

The necessary pH gradient may be created in many ways. One of the most convenient methods uses a series of buffer solutions containing monovalent ions provided by a salt of a strong base and weak acid e.g. sodium acetate (or, alternatively, a salt of a strong acid and weak base or yet again, a salt of a weak acid and weak base), and containing varying amounts of added weak acid (or weak base or both weak acid and weak base). If we consider the use of sodium acetate - acetic acid buffer it will be understood that the bulk of the electric current will be carried through the series of compartments by sodium ions passing progressively from the first compartment (the anodic side of the series) to the last compartment (the cathodic side) and by acetate ions moving in the opposite direction.

The ratios of the sodium ion and acetic acid concentrations in the various compartments are adjusted to give the required pH, so



- 8 -

that each isoelectric membrane separates a compartment on its anodic side having a pH lower than its pI from a compartment on its cathodic side having a higher pH. When electricity is passed through the apparatus arrangements must be made to continually restore cations to the first compartment (A) and anions to the last compartment (B) and at the same time to remove anions from compartment A and cations from compartment B. This is most easily done by adjusting the concentrations of the buffer salts in compartments A and B such that when equal volumes of liquid are circulated from A to B and from B to A at a rate determined by and proportional to the electric current flowing through the cell, the net transfer of buffer by circulation equals the net transfer by the electric current. There are many other possible ways of maintaining the concentrations in compartments A and B. For instance counterflow of ions can be performed electrically or fresh buffer solution can be continually passed through A and B and then to waste. The use of this method, involving one singly charged anion and one singly charged cation together with uncharged molecules of acid or base or both is particularly suitable where only a small range of isoelectric points is required. For a larger range use may be made of acids or bases which have multiple ionised forms having individual values not widely separated e.g. mellitic acid. This particular technique however involves the use of auxiliary electrodes in the various compartments.

Another method of establishing the pH gradient is by means of a mixture of carrier ampholytes which migrate in the electrical field until they reach a compartment having a pH equal to their



- 9 -

isoelectric point wherein they remain stationary. This is a more costly method but avoids the need for arrangements for counterflow described above when simple buffers are used.

#### ELECTROPHORESIS APPARATUS

- 5 It will be appreciated from the foregoing that the present invention also comprises a multi-diaphragm apparatus for isoelectric focussing containing a series of isoelectric membranes arranged in sequence of isoelectric point between the anode and cathode, the isoelectric point becoming increasingly alkaline towards the cathode.
- 10 The membranes in multi-diaphragm apparatus of the kind described may be arranged in any desired configuration, for example either as a horizontal series of vertically disposed membranes arranged side by side and separated by the customary spacers or as a vertical series e.g. in a nesting arrangement of membranes supported one above the other in
- 15 the vertical direction. One particularly convenient form involves membranes in sheet form resting one above the other and suitably spaced apart and arranged for gravity flow of the electrolytes through the various compartments from one end of the system to the other. With membranes in extended sheet form as described it will be necessary
- 20 to provide sealing along two opposite edges of the membranes in order to confine the liquid in the apparatus and to direct it in the desired direction through the apparatus. In all these cases it is a particularly attractive and preferred feature of the invention to provide separate pumping and cooling arrangements for each of the electrolyte circuits
- 25 for the various compartments.

Preferably the anode and cathode of the system are located in appropriate electrolyte baths at opposite ends of the apparatus each



- 10 -

such bath being separated from the membrane system by means of an ion exclusion membrane. At the anode end the ion exclusion membrane will be a highly negatively charged cation exchanger whereas at the cathode end the ion exclusion membrane will be a highly positively charged anion exchanger. By this means current is led into the apparatus at the anode by means of hydrogen ions only, and at the cathode end there is a corresponding counterflow of hydroxyl ions.

The invention will now be further described with reference to the accompanying drawings of which:-

Figure 1 is a schematic view of the principle of the electrophoresis apparatus of the invention,

Figure 2 is a sectional view of a practical arrangement of nesting membranes taken in the direction of electrolyte flow, and

Figure 3 is a transverse sectional view of the apparatus of Figure 2 taken across the direction of electrolyte flow.

Referring now to Figure 1 the apparatus consists of a stack of isoelectric membranes 1 defining between them compartments 2 into which the components of a mixture are to be separated. Four such membranes 1 are shown defining three compartments 2 but it will be understood that the system can be extended indefinitely in length. At opposite ends of the system are the electrodes. At the left-hand end a lead peroxide anode 3 is immersed in a dilute sulphuric acid compartment 4 and is electrically connected to the stack by means of a cation exchange membrane 5 so that all current is transported by hydrogen ions. The membrane 5 is separated from the first isoelectric membrane 1 by means of a compartment 6. At the other end a mild steel cathode 7 is immersed in a dilute sodium hydroxide compartment 8 and

is electrically connected to the stack by means of a highly positively charged anion exchange membrane 9 so that all current at this end of the apparatus is transported by hydroxyl ions. Hence only the elements of water are passed from the electrode compartments to the rest of the stack during passage of current. The membrane 9 is separated from the last isoelectric membrane 1 of the system by means of a compartment 10.

The apparatus thus comprises three separator compartments 2 with two additional compartments 6 and 8 and into all these compartments buffers at appropriate pH are introduced. By gravity or pumping devices a continuous flow is established in all compartments by circuits shown diagrammatically at 11 which include heat exchangers (not shown). A two-directional counterflow of electrolyte is arranged between compartment 6 and compartment 10 to restore electrolyte balance necessary because of continuous depletion of anions and cations as electric current passes.

Referring now to Figures 2 and 3, a nesting arrangement of ampholyte membranes 20 supported between strong plastic sheets 21 and 22 are mounted around a support member 23. The membranes 20 are separated by means of gauze layers 24 and outside the four membrane sandwich so formed there are positioned an outer anion exchange membrane 25 and an inner cation exchange membrane 26. Outside these are the electrodes, the cathode 27 being outermost and the anode 28 being innermost, both of which are similarly protected by gauzes.

The generally trough-shaped arrangement of membranes passes over a weir 29 so positioned that electrolyte flow through the system can be by means of gravity. Introduction of electrolyte from the right-



- 12 -

hand end of the system as shown and withdrawal of electrolyte from the left-hand part of the system as shown is achieved by means of separator devices 30 also of strong plastic film which diverge outwardly from the relatively narrow channel in between adjacent membranes 20 so as to facilitate introduction and withdrawal of electrolyte. As seen in Figure 3 the flow of electrolyte is confined within the sandwich by means of gasket sealing strips 31 extending along opposite longitudinal edges of the system. Fluid tightness is achieved by suitable clamping means (not shown). Typical membranes for use in the apparatus may be made by chemical methods as described in the following Examples.

#### EXAMPLE 1

Hardened filter papers (Whatman grade 541) are soaked in hot aqueous agarose (2% - 8% w/v) and the surplus agarose removed by pressing the paper between two warm glass plates. After the impregnated papers have cooled they are soaked for one hour in aqueous sodium hydroxide (2.5M) and then after blotting lightly they are suspended overnight in xylene containing epichlorhydrin (1% v/v). This cross-links the gel and strengthens it for subsequent treatment. The membranes are then soaked for one hour in sodium hydroxide (2.5M) and immersed for two hours in an alkaline solution of sodium chloroacetate freshly prepared by mixing equal volumes of sodium hydroxide solution (5.0M) and chloroacetic acid (2 M). After two hours the carboxylated membranes are rinsed in sodium hydroxide solution (2.5 M) and then soaked for two hours in 2.5 M sodium hydroxide containing diethanolamine (0.08 - 0.12M). After two hours the membranes are blotted lightly and suspended overnight in xylene containing epichlorhydrin (8% v/v) during which time the

- 13 -

epichlorhydrin reacts with the gel and links the diethanolamine to the gel. This procedure gives membranes with isoelectric point between pH 4.8 and 5.5.

EXAMPLE 2

5 The membrane is a filter paper impregnated with 4% agarose gel. It is soaked for 1.5 hours in a solution prepared from one or a mixture of the following reagents.

Acidic reagent

LKB Ampholine carrier ampholyte  
10 pH range 3.5 - 5, code 1809-111.

Basic reagent

A solution of chloracetic acid (47.25g) in water (100 ml) is added slowly with stirring to a solution of technical grade tetraethylene pentamine (90 ml) in water (100 ml). When  
15 addition is complete the solution is diluted with water to 300 ml. The solution is prepared by adding about 5 ml of Acidic Reagent or Basic Reagent or a total of about 5 ml of a mixture of these Reagents to 10% aqueous sodium hydroxide (40 ml).

After soaking the membrane is removed, lightly blotted, and  
20 then transferred to a solution (8% w/v) of epichlorhydrin in toluene and stood overnight.

Typical pI values obtained by varying the amounts of reagent used are as follows:-



- 14 -

	<u>Membrane</u>	<u>Acidic Reagent (ml)</u>	<u>Basic Reagent (ml)</u>	<u>pI</u>
	A	5	0	4 - 4.5
	B	4	1	4.5 - 5.0
	C	4	1.05	5.0 - 5.5
5	D	4	1.10	5.5 - 6.0
	X	0	5	above 10
	E (control)	0	0	-

EXAMPLE 3

The use of membranes A, B, C and D prepared as described in Example 2  
 10 and a comparison with control membrane E (non-isoelectric) is demonstrated  
 by the following experiments. For convenience the method is related to  
 the scheme shown in Figure 1 of the drawings.

The experiments were performed in a five compartment apparatus.  
 The area of the membranes was  $26.4 \text{ cm}^2$  and the current at the start of  
 15 each experiment was approximately 1.25 A i.e.  $47 \text{ mA/cm}^2$ . The contents  
 of each compartment 2 were circulated by means of pumps through external  
 coolers and reservoirs to form separate circuits. The liquids in the  
 end compartments i.e. 6 and 10 were circulated at a rate of about  
 500 ml/min, whilst the liquids in the intermediate compartments 2  
 20 were circulated at approximately 100 ml/min. The buffer solution  
 used was sodium pivalate.

The compositions and amounts of the solution in each circuit  
 are tabulated below. For convenience the compartments from left to  
 right in Figure 1 (i.e. 6 to 10) are referred to as circuits 1 to 5  
 25 respectively. In this Example, circuits 1 and 5 have such large  
 volumes that compositional changes are insignificant and therefore  
 the two-directional flow between them is omitted.



- 15 -

Circuit	1	2	3	4	5
Volume Litres	10	0.45	0.45	0.45	50.0
pH (calculated)	4.0	4.5	5.0	5.5	6.0
Ionic Concentration mM.Na <sup>+</sup>	11.4	6.7	6.7	6.7	67.0

In the first experiment Membrane A was placed between circuits (1) and (2), membrane B was placed between (2) and (3), membrane C was placed between (3) and (4), and membrane D between circuits (4) and (5).

A mixture of bovine serum Albumin (1g) and horse heart cytochrome  
 10 approx. (0.15g) was dissolved in the solution circulating in circuit 4.  
 The analytical results are shown in Table II.

BUREAU  
OMPI

	1	2	3	4	5
Time					
pH	4.0	4.55	5.05	5.50	6.05
Minutes					
Volume ml.	10,000	450	450	450	50,000
Conductivity (ohms <sup>-1</sup> cm <sup>-1</sup> x10 <sup>6</sup> )	19.5	13.5	13.5	13.5	100.5
Conc. BSA	-	0	0	2.2	-
Conc. Cytochrome Mg/ml	-	0	0	0.325	-
Time					
pH	-	4.55	5.05	5.50	-
Minutes					
Volume ml.	-	450	450	450	-
Conductivity (ohms <sup>-1</sup> cm <sup>-1</sup> x10 <sup>6</sup> )	-	-	-	-	-
Conc. BSA	-	0	0.48	-	-
Conc. Cytochrome Mg/ml	-	0	0	0.22	-

BUREAU

[illegible]

- 18 -

This Table demonstrates a progressive transference of bovine serum albumin from circuit 4 to circuit 3 and progressive reduction of the cytochrome component in circuit 4. The cytochrome transfers to circuit 5 which is of such large volume as to make analysis difficult. The stable conditions of pH and conductivity due to insignificant electroendosmosis in this experiment are clearly apparent.

In contrast Table III shows results obtained when the membrane C between circuits (3) and (4) is substituted by the control  
10 membrane E.



### TABLE III

		1	2	3	4	5
Time	pH	4.0	4.50	5.01	5.55	6.05
Minutes	Volume ml.	10,000	450	450	450	50,000
0	Conductivity (ohms <sup>-1</sup> cm <sup>-1</sup> x10 <sup>6</sup> )	18.5	13.5	13.5	13.6	101.5
	Conc. BSA Mg/ml	-	0	0.	2.2	-
	Conc. Cytochrome Mg/ml	-	0	0	0.23	-
15	Time					
	pH	-	4.50	5.00	5.45	-
Minutes	Volume ml.	-	450	425	475	-
	Conductivity (ohms <sup>-1</sup> cm <sup>-1</sup> x10 <sup>6</sup> )	-	-	-	-	-
	Conc. BSA Mg/ml	-	0	0	-	-
	Conc. Cytochrome Mg/ml	-	0	0	0.16	-



- 20 -

TABLE III/contd.

Time Minutes	pH	Volume ml.	Conductivity (ohms <sup>-1</sup> cm <sup>-1</sup> x10 <sup>6</sup> )	Conc. BSA Mg/ml	Conc. Cytochrome Mg/ml
30	3.95	-	16	-	-
	4.45	440	11.5	0	0
	4.95	385	5.0	0	0
	5.35	505	26	-	0.11
	6.01	-	100.6	-	-

- 21 -

In Table III the large endosmosis effect is shown by the increase of volume in circuit 4 and its decrease in circuit 3. The endosmotic effect opposes the passage of the albumen to such an extent that none passes into circuit 3. The pH drops 5 continually in circuit 4 due to passage of bulk fluid from circuit 3. The conductivity, which is equal in circuits 2, 3 and 4 at the start of the separation, is dramatically altered in these circuits by the 30 minute stage. It was necessary to abandon the experiment at this point.



CLAIMS

1. An electrophoresis membrane of known isoelectric point and having buffering capacity at its isoelectric point whereby the tendency for electroendosmosis to occur during electrophoresis is reduced.
- 5 2. A membrane according to claim 1 having high concentrations of acidic and basic groups the level of which has been adjusted in preparation to give the membrane an isoelectric point in a defined pH range.
3. A membrane according to claim 1 or 2, being a chemically  
10 treated agarose or polyacrylamide gel.
4. A membrane according to claim 1, 2 or 3, being a supported membrane.
5. A membrane according to any of claims 1 to 4, comprising ampholyte molecules attached to a substrate.
- 15 6. A membrane according to claim 5, in which the ampholyte molecules are chemically attached to the substrate.
7. A membrane according to claim 6, in which the attachment is by means of an intermediate linking group.
8. A membrane according to any of the preceding claims, having  
20 an isoelectric point in the range pH 4 to 6.
9. A method of separating a substance by membrane electrophoresis in which the substance is isoelectrically focussed in an electrolyte pH gradient by means of a membrane according to any of claims 1 to 8 which is located between electrolyte of pH lower than its  
25 isoelectric point on the anodic (+) side of the membrane and electrolyte of pH higher than its isoelectric point on its cathodic (-) side.



10. A method according to claim 9, using a series of such membranes having isoelectric points increasing towards the cathode and an electrolyte pH gradient of increasing pH in the same direction.
11. A method according to claim 9 or 10, in which the electrolyte
- 5 pH or pH gradient is provided by monovalent buffering ions.
12. A method according to claim 11, in which the buffering ions comprise ions of a weak organic acid, or a weak organic base, or both.
13. A method according to any of claims 9 to 12, in which the
- 10 pH difference between opposite sides of the or each membrane is of the order of 0.5 units.
14. A method according to any of claims 9 to 13, in which proteins or peptides are separated.
15. A membrane electrophoresis apparatus for isoelectric focussing
- 15 comprising a series of membranes according to any of claims 1 to 8 arranged in sequence of increasing isoelectric points towards the cathode (negative electrode) and means for establishing a series of circulating electrolyte zones having a pH gradient of increasing pH in the same direction.
- 20 16. Apparatus according to claim 15, comprising means for mounting membranes in a generally vertical series.
17. Apparatus according to claim 16, in which the membranes are in sheet form and arranged in a nesting configuration with edge sealing.
- 25 18. Apparatus according to claim 17, in which electrolyte flow through the compartments between the membranes is by gravity.

- 24 -

19. Apparatus according to any of claims 15 to 18, in which each electrolyte zone in the pH gradient is provided with cooling means.

20. Apparatus according to any of claims 15 to 19, having an anode in an acidic compartment separated from the membrane series by an  
5 anion exclusion membrane so that electricity is carried through the latter exclusively by hydrogen ions.

21. Apparatus according to claim 20 in which the anode is lead peroxide in dilute sulphuric acid.

22. Apparatus according to any of claims 15 to 21, having a cathode  
10 in an alkaline compartment separated from the membrane series by a cation exclusion membrane so that electricity is carried through the latter exclusively by hydroxyl ions.

23. Apparatus according to claim 22, in which the cathode is mild steel in a dilute solution of an alkali metal hydroxide.



1/2







Fig. 1

2/2



<b>I. CLASSIFICATION OF SUBJECT MATTER</b> (If several classification symbols apply, indicate all) <sup>3</sup> According to International Patent Classification (IPC) or to both National Classification and IPC G 01 N 27/26; B 01 D 13/02		
<b>II. FIELDS SEARCHED</b> Minimum Documentation Searched <sup>4</sup>		
Classification System	Classification Symbols	
Int. Cl. <sup>2</sup>	G 01 N 27/26; B 01 D 13/02; B 01 D 43/00; B 01 D 57/00; B 01 D 13/04; C 08 J 5/22.	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched <sup>5</sup>		
<b>III. DOCUMENTS CONSIDERED TO BE RELEVANT</b> <sup>14</sup>		
Category <sup>6</sup>	Citation of Document, <sup>15</sup> with indication, where appropriate, of the relevant passages <sup>17</sup>	Relevant to Claim No. <sup>18</sup>
	GB, A, 1121449, published 1968, July 24, see claims 1 and 2 (BAUSCH & LOMB INC.) --	1,3
	US, A, 3948743, published 1976, April 6, see: claims 1 and 7; abstract; column 3, lines 30-32; column 4, line 42 to column 5, line 13 (table included) (J.F. MONTHONY) --	1,3
P,E	DE, A, 2638526, published 1977, July 14, see: "Patentanspruch" 1; page 3; page 5, last paragraph (FUJI PHOTO FILM CO. LTD) --	1,9,14
P,E	FR, A, 2334951, published 1977, July 8, see: "revendications" 1-5, 12, 14; page 1, lines 25-30; page 3, line 15 to page 5, line 18 (AMINKEMI AB) & DE, A, 2656162, published 1977, September 29 --	1,3,9,10, 14,15
./. .		
* Special categories of cited documents: <sup>16</sup> "A" document defining the general state of the art "E" earlier document but published on or after the international filing date "L" document cited for special reason other than those referred to in the other categories "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but on or after the priority date claimed "T" later document published on or after the international filing date or priority date and not in conflict with the application, but cited to understand the principle or theory underlying the invention "X" document of particular relevance		
<b>IV. CERTIFICATION</b>		
Date of the Actual Completion of the International Search <sup>1</sup> 12th September, 1978		Date of Mailing of this International Search Report <sup>2</sup> 15th September, 1978
International Searching Authority <sup>1</sup> European Patent Office-		Signature of Authorized Officer <sup>20</sup> 

## FURTHER INFORMATION CONTINUED FROM THE SECOND SHEET

A	FR, A, 1527883, published 1968, June 7 see the "résumé" (ACADEMIA REPUBLICII SOC. ROMANIA)	3
A	FR, A, 1316726, published 1963, see "résumé" 1 and 2 (AMERICAN MACHINE & FOUNDRY CO.)	2
A	GB, A, 1255418, published 1971, December 1 (LKB-PRODUKTER AB)	./..

V. ☐ OBSERVATIONS WHERE CERTAIN CLAIMS WERE FOUND UNSEARCHABLE <sup>10</sup>

This international search report has not been established in respect of certain claims under Article 17(2) (a) for the following reasons:

1. ☐ Claim numbers \_\_\_\_\_, because they relate to subject matter <sup>12</sup> not required to be searched by this Authority, namely:

2. ☐ Claim numbers \_\_\_\_\_, because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out <sup>13</sup>, specifically:

VI. ☐ OBSERVATIONS WHERE UNITY OF INVENTION IS LACKING <sup>11</sup>

This International Searching Authority found multiple inventions in this international application as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims of the international application.

2. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims of the international application for which fees were paid, specifically claims:

3. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claim numbers:

## Remark on Protest

- ☐ The additional search fees were accompanied by applicant's protest.  
☐ No protest accompanied the payment of additional search fees.

## FURTHER INFORMATION CONTINUED FROM THE SECOND SHEET

- |   |   |
|---|---|
| A | US, A, 3240692, published 1966, March 15<br>(T.H. DONNELLY)         |
| A | FR, A, 1223635, published 1960, June 17<br>(TAKEDA PHARM. IND. LTD) |

V. ☐ OBSERVATIONS WHERE CERTAIN CLAIMS WERE FOUND UNSEARCHABLE <sup>10</sup>

This International search report has not been established in respect of certain claims under Article 17(2) (a) for the following reasons:

1. ☐ Claim numbers \_\_\_\_\_, because they relate to subject matter <sup>12</sup> not required to be searched by this Authority, namely:
2. ☐ Claim numbers \_\_\_\_\_, because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out <sup>13</sup>, specifically:

VI. ☐ OBSERVATIONS WHERE UNITY OF INVENTION IS LACKING <sup>11</sup>

This International Searching Authority found multiple inventions in this international application as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims of the international application.
2. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims of the international application for which fees were paid, specifically claims:
3. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claim numbers:

## Remark on Protest

- ☐ The additional search fees were accompanied by applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

**THIS PAGE BLANK (USPTO)**